

5.6 PUBLIC TOILET POLICY

Date Adopted	Next Review	Officer Responsible
1 October 2012	1 September 2015	Manager, Sports Recreation & Environment

Policy Purpose:

The overall aim of this policy is to set guidelines in the development, maintenance and placement of public toilets within the Rotorua District. The success of this policy can be gauged in the delivery of safe, hygienic, accessible, well-maintained and strategically located toilets that meet the needs of residents and visitors alike.

Scope of Policy:

This policy applies to all public toilets located within the Rotorua District that are owned and operated by Council either through the Parks and Recreation Department or City Services Operations. It includes facilities located at cemeteries, parks, sports facilities, commercial centres and the Redwoods. It excludes toilets in permanently staffed Council buildings.

(Please note that conditions and stipulations related to 'Public Toilet Policy' are to be read in conjunction New Zealand Standard 4241: Public Toilets)

Glossary:

CPTED: Crime Prevention through Environmental Design Principles

Public Toilet: In terms of this policy means any toilet outside of a permanently staffed Council building that is provided for the use of the general public by the Rotorua District Council.

5.6.1 Location and Siting

Policy:

Rotorua District Council will provide access to public toilets in the following locations:

- Areas of high pedestrian traffic or areas of public assembly
- Within the central business district and major retail areas.
- Areas used for outdoor recreational purposes (e.g. camp sites, beaches, lakes, reserves, etc)

5.6.2 Accessibility

Policy:

All public toilets shall be easily visible and accessible with consideration for specific provisions for the elderly, disabled and young children.

Normal operating hours of public toilets shall be between 6:00am to 8:00pm. These hours may be varied in keeping with estimated public demand and expectations or seasonal changes in use.

All public toilets shall have at least one disabled toilet available for use during normal operating hours.

5.6.3 Cleanliness

Policy:

All public toilets shall be clean, hygienic, well-maintained and pleasant.

Increased cleaning frequencies may need to be implemented to maintain the expected level of cleanliness within the toilet facility during the course of events occurring at the same location.

Toilet cleaning regimes may be altered during the year to allow for more efficient use of available resources.

5.6.4 Safety

Policy:

Public toilets shall be situated in high activity areas with greater foot traffic to reduce the likelihood of undetected and unwanted behaviour.

Entrances to toilets will be accessible and visible, facing public areas with minimal vegetation to avoid obstructed lines of sight

Additional safety precautions such as no-slip floors, graffiti resistant coatings on walls and fixtures, and vandal proof equipment shall be used.

Where possible, new toilets shall be constructed using Crime Prevention through Environmental Design (CPTED) principles.

5.6.5 Lighting

Policy:

The interior of public toilets shall be adequately lit. Natural light shall be preferred, wherever possible.

Illumination through skylights, high windows and other relevant features (including solar lighting) shall be incorporated into the design as appropriate.

129

All 24 hour toilets shall have adequate interior and exterior lighting, in accordance with NZS 1158: Lighting for Roads and Public Spaces, Category C.

5.6.6 Signage

Policy:

International symbols for male, female unisex and disabled shall be used on signage in compliance with NZS 8603: Design and Application of Outdoor Recreational Symbols.

Location of toilets shall be signposted in convenient places along major traffic or pedestrian routes and where toilets are not immediately visible, distance to these shall be indicated. Opening hours shall be clearly visible and posted outside toilets, along with Council's contact details to report damage, repairs or other issues.

Details of toilet locations shall be incorporated into Council publications such as websites, maps, guides, leaflets and GPS based tourism application for personal communication devices, in order to improve knowledge or public toilet availability and enhance the perception of Rotorua city as a visitor friendly location.

5.6.7 Design

Policy:

High quality design that is aesthetically consistent with the surrounding environment is recommended.

Special consideration shall be given to conservation and sustainability principles to minimise environmental impact (e.g. use of natural light, passive ventilation, water-saving devices, etc)

Where able to be all Public Toilets shall be connected to a reticulated sewage system.

Where reticulation is not available then a wastewater system complying with NZS 1547:2012 On-site Domestic Wastewater Management Standards shall be provided.

5.6.8 Toilet Classification

Policy:

The following classifications shall be adopted to guide in the design and maintenance decisions associated with all Public Toilets within the Rotorua District.

Tier	Type of Facility	Design Expectations	Fitout Expectation	Levels of Service
1	Toilets at highly	The design should enhance	High quality	Expectation These units shall be
	frequented premier	the destination. The use	fittings, interior	inspected and cleaned
	tourist destinations	experience is exceptional.	and exterior	continually throughout
	and in Rotorua CBD	Design & context may integrate or contrast with	lighting, international	the day. Sanitising procedures should be
		context to appropriately	signage,	carried out on a weekly
		improve the attraction.	maintenance	basis, or more
		Should be designed	checks daily.	frequently according to
		conceptually by a creative	•	high use.
		professional through a		
		competition. The design		
		needs to be accessible &		
		have a focus on aesthetic treatment.		
2	Toilets at highly	Design should be suitable for	Quality fittings,	These units shall be
	frequented	context with some	interior and	inspected and cleaned
	destinations	investment in appearance.	exterior lighting,	at least twice a day.
		Accessible and pleasant use	international level	Sanitising procedures
		experience. The building	signage,	should be carried out on
		form & colour need to integrate with the	maintenance checks every one	a weekly basis, or more frequently according to
		environment. This could be	to two days.	high use.
		either a unique design or	to two days.	mgn use.
		standard design.		
3	Toilets at	The design should be a	Quality fittings,	These units shall be
	sportsfields/facilities	standard design that is	interior lighting,	inspected and cleaned
	in Rotorua suburbs	sympathetic to the urban or	possible exterior	at least two-three times
		residential context. A degree of aesthetic treatment but	lighting, signage,	a week. Sanitising
		not a significant cost. The	maintenance checks every	procedures should be carried out on a bi-
		building form & colour need	week/two weeks.	weekly basis, or more
		to integrate with subject site	TOCKY COVO WCCKS.	frequently according to
		and context.		high use.
4	Toilets at rural	Standardised utilitarian	Basic fittings,	These units shall be
	reserves or less	structures. Building form and	interior lighting	inspected and cleaned
	frequented areas	colour integrate the	(only passive	once every two weeks.
		structure with the subject	natural lighting	Sanitising procedures
		context.	acceptable). Maintenance	should be carried out on
			checks monthly.	a monthly basis. Or more frequently
			CHECKS HIUHUHY.	according to high use.
				according to mgn use.

Tier	Type of Facility	Design Expectations	Fitout Expectation	Levels of Service
				Expectation
5	Toilets on back-	Standardised utilitarian	No quality	The frequency of
	country tramping	structures painted to	expectation, no	inspection, cleaning,
	tracks or other areas	integrate the structure	maintenance	and sanitising for these
	with very infrequent	within the context of the	unless specifically	units shall be
	usage.	site. The unit needs only be	requested.	determined by assessing
		as accessible to the extent		the characteristics of
		allowed by the access to the		the individual toilets,
		facility.		location and number of
				users, in accordance
				with NZS 4241- Public
				Toilets.

5.6.9 Maintenance and Cleaning

Policy:

Public toilets will be will-maintained and regularly serviced. Servicing frequency will vary depending on the tier level, level of use and user expectations. The servicing frequency may be seasonally adjusted to maximise efficiencies based on user numbers. Cleaning and servicing schedules shall be in accordance with the levels prescribed in New Zealand Standard 4241 – Public Toilets.

Levels of Service statements for Tiers 1, 2 &3 toilets shall be posted and visible at each toilet block. Regular monitoring and inspections will be carried out to guarantee adequate levels of sanitation and to assist with determining priorities for upgrades and renewals.

Necessary maintenance shall be carried out immediately and graffiti will be removed within 24 hours of notification. Frequency of reactive and programmed repairs and maintenance will ensure minimum disruption to the facilities and services available to users.

Council will conduct and/or participate in annual surveys to determine user satisfaction and related issues.

Where a Public Toilet is located within 200 metres of a lake edge and is currently operating an on-site effluent treatment system, the system shall be pumped out at no greater than 3 years and the results submitted to the Bay of Plenty Regional Council.

5.6.10 Establishment Criteria

Policy:

Establishment of new public toilet facilities within the Rotorua District will be assessed on the basis of the following criteria:

- Current and future demand
- Visitor growth
- Population growth
- Deficiencies (perceived and actual) in current provision
- Development of new facilities or destinations (e.g. reserves, recreation)

Where the need for new public toilet facilities has been approved, Council will consider the following possibilities for establishment:

- Private development and/ or sponsorship
- Joint venture/partnership with private sector
- Fully owned and operated by Council

5.6.11 Disestablishment Criteria

Policy:

Existing public toilets facilities within the Rotorua District that have been assessed as unsuitable for use due to condition of structure, location or other factors, shall be subject to one of the following courses of action:

- Renovate: subject to condition assessment and cost
- Replace: subject to condition assessment and cost
- Relocate: subject to condition assessment and changes in demand/use
- Remove: subject to condition assessment and changes in demand/use

Consideration should be given to each toilet as to the merits of each of the above courses of action based on the following criteria:

- Current location of facility
- Levels of use
- Location
- Cost

Where the need for provision of an existing public toilet cannot be justified subsequent to consultation with the community, the facility shall be disestablished.

Decommissioned toilets that are subject to repeated acts of vandalism shall be disestablished.

RELEVANT/RELATED LEGISLATION/BYLAWS AND POLICES

Rotorua District Council is governed by the following legislation with regard to the provision of public toilet facilities:

- Building Act (1991&2004)
- Health Act (1956)
- Health and Safety in Employment Act (1992)
- Local Government Act (1974 & 2002)
- Reserve Act (1977)
- Resource Management Act (1991)

Council planning documents relevant to this policy include the Annual Plan, District Plan and Long Term Council Plan.